

according to Regulation (EC) No 1907/2006 and 1272/2008, Hazard Communication Standard 29 CFR 1910 (USA), WHS Regulations Australia, JIS Z 7253 (2012) Japan

Accura® 60

Revision Date: June 12, 2017

1. IDENTIFICATION OF THE PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Identification of the mixture: Accura® 60

1.2 Use of the preparation: For use with SLA systems

1.3 Company/undertaking identification:

3D Systems, Inc.
333 Three D Systems Circle
Rock Hill, South Carolina U.S.A.
Phone: 803.326.3900 or
Toll-free Phone: 800.793.3669

e-mail: moreinfo@3dsystems.com Chemical Emergency:

Chemical Emergency: 800.424.9300 – Chemtrec

3D Systems Europe Ltd.

Mark House, Mark Road

Hemel Hempstead

Herts HP2 7 United Kingdom

Phone: +44 144-2282600

3D Systems / Australia

5 Lynch Street

Hawthorn, VIC 3122

+1 03 9819-4422

e-mail: moreinfo@3dsystems.com

Phone: +44 144-2282600 e-mail: moreinfo@3dsystems.com

Chemical Emergency: +1 703.527.3887 - Chemtrec

+1 703.527.3887 - Chemtrec

Chemical Emergency:

+(61) 29037.2994 - Aus Chemtrec

2. HAZARDS IDENTIFICATION

2.1 Classification

GHS: Regulation (EC) No. 1272/2008, HazCom 2012, Australian Dangerous Goods Code:

Serious eye irritation	Category 2	H319
Skin irritation	Category 2	H315
Skin Sensitization	Category 1	H317
Aquatic environment – long-term hazard	Category 3	H412

Regulation (EC) 67/548/EEC and 1999/45/EC:

Xi, R 36/38, R 43, R 52/53

2.2 Label Elements

Regulation (EC) No, 1272/2008:

Hazard pictograms and signal word:



GHS07

Signal word: Warning

Hazard determining components of labelling:

3,4- Epoxycyclohexylmethyl 3,4-epoxycyclohexane carboxylate

Hazard statements:

H319: Causes serious eye irritation

H315: Causes skin irritation

H317: May cause an allergic skin reaction

H412: Harmful to aquatic life with long lasting effects

Precautionary statements:

P280: Wear protective gloves, protective clothing, eye protection

P302+350: If on skin, wash with soap and water

P305+351+338: If in eyes, rinse cautiously with water for several minutes. Remove contact lenses if present and

easy to do. Continue rinsing

P410+403: Protect from sunlight. Store in a well-ventilated place

P501: Dispose of contents/container in accordance with local/regional regulations



according to Regulation (EC) No 1907/2006 and 1272/2008, Hazard Communication Standard 29 CFR 1910 (USA), WHS Regulations Australia, JIS Z 7253 (2012) Japan

Accura® 60

Revision Date: June 12, 2017



NFPA Ratings

0 = Minimal

1 = Slight

2 = Moderate 3 = Serious

4 = Severe

Hazardous Materials Identification System (HMIS):

(Degree of hazard: 0 = low, 4 = extreme);

Health 2
Flammability 1

Physical Hazards 1

Personal Protection:

Skin, eye protection

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Chemical characterization: **Description**: Organic mixture

3.2 Dangerous components:

5.2 Danigorous componento:		Classification			
Chemical name	CAS-No	EC-No	%	Regulation (EC) 1272/2008	Regulation 67/548/EEC, 1999/45/EC
3,4- Epoxycyclohexylmethyl 3',4'- epoxycyclohexane carboxylate	2386-87-0	219-207-4	40-60	Eye Irrit. 2, H319 Skin Irrit.2, H 315 Skin Sens.1, H 317 Aqu. Chron. 3, H 412	Xi R36/38, R43, R52/53
Ethoxylated pentaerytritol tetraacrylate	144086-02-2	604-394-0	12-22	Eye Irrit. 2, H319 Aqu. Chron. 2, H 411	Xi, N R36, R51/53
Mixture containing triarylsulfonium salt: 50% Propylene Carbonate 50% Mixed triarylsulfonium salts	108-32-7, 71449-78-0, 89452-37-9	203-572-1 403-500-0	2-7	Eye Irrit. 2, H319 Skin Sens 1, H317 Aqu. Acute 1, H400 Aqu. Chron.1, H410	Xi, N R36, R43, R50/53

4. FIRST AID MEASURES

- 4.1 General Information: Ensure that eyewash stations and safety showers are close to the workstation location.
- **4.2 In case of inhalation:** May cause respiratory irritation. Move affected person to fresh air. If respiratory irritation occurs, if breathing becomes difficult seek medical attention immediately.
- **4.3 In case of skin contact:** May cause irritation or sensitization by skin contact, including redness and/or swelling. Immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse.
- **4.4 In case of eye contact:** Irritating to eyes. Causes redness, swelling and pain. Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if symptoms persist.
- **4.5** In case of ingestion: Irritating to mouth, throat and stomach. If ingested, drink plenty of water and seek immediate medical attention. Do not induce vomiting.
- **4.6 Self-protection of the first aider:** Put on appropriate protective equipment (see section 8). Move exposed person to fresh air. Remove contaminated clothing and shoes.



according to Regulation (EC) No 1907/2006 and 1272/2008, Hazard Communication Standard 29 CFR 1910 (USA), WHS Regulations Australia, JIS Z 7253 (2012) Japan

Accura® 60

Revision Date: June 12, 2017

5. FIRE-FIGHTING MEASURES

- **5.1 Suitable extinguishing media:** Water mist, dry chemical, carbon dioxide, or appropriate foam.
- 5.2 Extinguishing media which must not be used for safety reasons: High volume water jet.
- **5.3** Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases: Thermal decomposition products can include CO₂, CO and smoke.
- **5.4 Special protective equipment for fire-fighters:** Wear full protective clothing, including helmet, self-contained positive-pressure or pressure demand breathing apparatus, protective clothing and facemask.
- **5.5 Additional information:** Move container from area if it can be done without risk. Cool containers with water spray. Avoid inhalation of material or combustion by-products.

6. ACCIDENTAL RELEASE MEASURES

- **6.1. Personal precautions:** Keep unnecessary personnel away. Wear appropriate protective equipment and clothing. Consult expert immediately.
- **6.2 Environmental precautions:** Stop the flow of material, if this is without risk. Ventilate contaminated area. Eliminate sources of ignition. In case of contamination of aquatic environment inform local authorities.
- **6.3 Methods for cleaning up:** Wear appropriate protective equipment and clothing. Absorb spillage with suitable absorbent materials. Place all waste in an appropriate container for disposal. The material and its container must be disposed of as hazardous waste. Keep away from sources of ignition.

7. HANDLING AND STORAGE

- **7.1 Handling** Provide adequate ventilation. Use suitable protective equipment. Avoid contact with skin and eyes. Do not breathe vapors or mist. Avoid ignition sources. Do not allow to enter drains or watercourses.
- **7.2 Storage:** Store sealed in the original container at room temperature. Keep this material indoors in a cool, dry, well ventilated place. Store out of direct sunlight or UV light sources. Storage Temperature: below 35 °C / 95 °F. Storage class 10, environmentally hazardous liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure limit values:

General Product Information: No occupational exposure limits (PEL/TWA) have been established for this product.

Component Analysis:

Component	Component Manufacturer IEL (Internal Exposure Limit)
3,4- Epoxycyclohexylmethyl 3',4'-epoxycyclohexane carboxylate	NA NA
Propylene Carbonate	NA
Antimonate mixture	0.5mg/m³ MAK (Switzerland, Netherlands, Austria) 0.5 mg/m³ VME (France) 0.5 mg/m³ TWA (Portugal, Finland, Norway, Ireland, Denmark) 0.5 mg/m³ VLA-ED (Spain) 0.5 mg/m³ NDS (Poland)

8.2 Exposure controls

Technical measures to prevent exposure: Use local exhaust ventilation.

Instructual measures to prevent exposure: When using, do not eat, drink or smoke. Wash hands after handling and before eating, smoking and using the lavatory and at the end of the day.



according to Regulation (EC) No 1907/2006 and 1272/2008, Hazard Communication Standard 29 CFR 1910 (USA), WHS Regulations Australia, JIS Z 7253 (2012) Japan

Accura® 60

Revision Date: June 12, 2017

Personal protection equipment:

Respiratory protection: If ventilation cannot effectively keep vapor concentrations below established limits, appropriate certified respiratory protection must be provided (e.g. 3M 6000 with organic vapor cartridge A2 or half mask 3M 4251).

Hand protection: Use impervious nitrile gloves.

Eye protection: Wear safety glasses or chemical goggles.

Body protection: Use apron and closed shoes.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Appearance: Physical state: Liquid Colour: Slightly blue

Odour: Mild

9.2 Important health, safety and environmental information

pH (20 °C): NA Melting point/range (°C): NA Boiling point/range (°C): NA 150°C Flash point (°C): Ignition temperature (°C): NA Vapour pressure (°C): NA Density (g/cm3): 1.1 Bulk density (kg/m3): NA

Water solubility (20°C in g/l): slightly soluble

Partition coefficient: NA n-Octanol/Water (log Po/w): NA

Viscosity, dynamic (mPas): 200-250 (30°C)

Dust explosion hazard: NA Explosion limits: NA

10. STABILITY AND REACTIVITY

- **10.1 Conditions to avoid:** Avoid exposure to heat and light. Take necessary actions to avoid static electricity discharge.
- 10.2 Materials to avoid: Oxidizing materials, strong acids and strong bases.
- **10.3 Hazardous decomposition products:** Carbon dioxide, carbon monoxide and other toxic fumes can be released at high temperatures or upon burning.

11. TOXICOLOGICAL INFORMATION

11.1 Toxicokinetics, metabolism and distribution: NA

11.2 Acute effects (toxicity tests)

Component	LD50 Oral	LD50 Dermal
3,4- Epoxycyclohexylmethyl 3',4'-epoxycyclohexane carboxylate	5000 mg/kg (rats)	>23400 mg/kg (rabbits)
Ethoxylated pentaerytritol tetraacrylate	> 5000 mg/kg (rat)	Non skin irritant
Propylene Carbonate	20700 mg/kg (mouse)	>20 ml/kg (rabbit)
Antimonate mixture	>2000 mg/Kg (rats)	>2000 mg/Kg (rabbits)

Irritant and corrosive effects: Irritating Irritation to respiratory tract: NA Sensitisation: Causes sensitisation



according to Regulation (EC) No 1907/2006 and 1272/2008, Hazard Communication Standard 29 CFR 1910 (USA), WHS Regulations Australia, JIS Z 7253 (2012) Japan

Accura® 60

Revision Date: June 12, 2017

11.3 Experiences made in practice

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

11.4 General remarks:

Carcinogenicity: None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

12. Ecological information

12.1 Ecotoxicity: The aquatic toxicity of the product is unknown; however based on components, it is predicted that this material may be toxic to aquatic organisms or cause long-term adverse effects in the aquatic environment. Prevent contamination of soil, drains and surface waters.

Component	Data
	EC50/48h – 40 mg/l (daphnia magna)
3,4- Epoxycyclohexylmethyl 3,4-epoxycyclohexane carboxylate	LC50/96h – 24 mg/l (onkorynchus mykiss)
	EC50/24h – 4.4 mg/l (daphnia)
Antimonate mixture	EC50/48h – 0.68 mg/l (daphnia)

- 12.2 Mobility: No information available for product.
- 12.3 Persistence and degradability: No information available for product.
- 12.4 Results of PBT assessment: No information available for product
- 12.5 Other adverse effects: No information available for product

13. DISPOSAL CONSIDERATIONS

- **13.1 Appropriate disposal / Product:** Do not contaminate drains, soil or surface waters with this material or its container. Reduce waste by attempting to utilize product completely. Dispose of this container and its contents in accordance with all local, state, and federal regulations. Do not reuse or refill.
- 13.2 Waste codes / waste designations according to EWC / AVV: 070208
- 13.3 Appropriate packaging: NA
- **13.4 Additional information:** Prior to disposal 3D Systems recommends consulting an approved waste disposal firm to ensure regulatory compliance.

14. TRANSPORT INFORMATION

14.1 Land transport (ADR/RID/GGVSE): Not regulated

14.2 Sea transport (IMDG-Code/GGVSee): Not Regulated

14.3 Air transport (ICAO-IATA/DGR): Not Regulated

15. REGULATORY INFORMATION

15.1 EU regulations

EINEC/ELINCS/NLP: All materials are listed

REACH Annex XVII: None listed

15.2 EU-National regulations

Wassergefährdungsklasse (water hazard class, Germany): WGK 2: Hazard to waters



according to Regulation (EC) No 1907/2006 and 1272/2008, Hazard Communication Standard 29 CFR 1910 (USA), WHS Regulations Australia, JIS Z 7253 (2012) Japan

Accura® 60

Revision Date: June 12, 2017

15.3 US FEDERAL

TSCA: All materials are listed on the TSCA Inventory or are not subject to TSCA requirements SARA 302 EHS List (40 CFR 355 Appendix A): None listed SARA 313 (40 CFR 372.65): Antimony Compounds (category N010) CERCLA (40 CFR 302.4): None listed

15.4 Australian regulations

SUSDP, Industrial Chemicals Act 1989:

Australian Inventory of Chemical Substances, AICS: Listed

15.5 Japanese regulations

Industrial Health and Safety Law Article 57-2: (Cabinet Order 38, antimony and its compounds,

excludes materials containing ≤1%)

Hazardous material not applicable
Organic solvent poison prevention rule ordinance on prevention of hazard due to specified chemical substances

not applicable not applicable

Lead Poisoning Prevention Rule not applicable

Poison and Deleterious Substance Control law antimony compounds: hazardous substance

PRTR and Promotion of Chemical Class 1 designated substances (Cabinet Order 25, antimony

Management law and its compounds, excludes materials containing ≤1%)

Fire Services Act Category 4, Class 3, oil

Explosives Law not applicable
High pressure gas safety law not applicable
Export Trade Control Order applicable

Waste Disposal and Public Cleaning Law applicable, industrial waste

16. OTHER INFORMATION

16.1 Relevant Hazard Statements (number and full text) referred to in sections 2 and 3 (according to (EC) No. 1272/2008):

Skin Irrit. 2, H 315- Skin irritation, category 2, H 315: Causes skin irritation

Skin Sens. 1, H 317- Skin sensitization, category 1, H317: May cause an allergic skin reaction

Eye Irrit. 2, H319- Serious eye irritation, category 2, H319: Causes serious eye irritation

Aqu.Chron. 3, H412- Aquatic environment – long-term hazard, category 3, H412: Harmful to aquatic life with long lasting effects

Aqu. Chron. 2, H 411- Aquatic environment – long-term hazard, category 2, H411: Toxic to aquatic life with long lasting effects

Aqu. Acute 1, H400- Aquatic environment- acute hazard, category 1, H400: Very toxic to aquatic life

Aqu. Chron.1, H410- Aquatic environment-long term hazard, category 1, H410: Very toxic to aquatic life with long lasting effects

Relevant R-Phrases (number and full text) referred to in sections 2 and 3:

R36: Irritating to eyes.

R36/38- Irritating to eyes and skin

R43: May cause sensitization by skin contact

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16.2 Further information:

SDS Creation Date:.....April 22, 2008 SDS Revision #:.....05-A SDS Revision Date:June 12, 2017

Reason for Revision:.....Update header, section 1, 8.



according to Regulation (EC) No 1907/2006 and 1272/2008, Hazard Communication Standard 29 CFR 1910 (USA), WHS Regulations Australia, JIS Z 7253 (2012) Japan

Accura® 60

Revision Date: June 12, 2017

www.3dsystems.com 800.793.3669 (Toll-free in the US GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.) 803.326.3900 (Outside the U.S. GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.) +44 144-2282600 (Europe GMT+01:00; Mon – Fri, 08:00 a.m. - 17:00 p.m. MEZ)

DISCLAIMER OF LIABILITY: The following supersedes any related provision in your company's forms, letters, and agreements from, by or with 3D Systems Corporation. 3D Systems, Inc. makes no warranty whether expressed or implied, including warranties of merchantability or of fitness for a particular purpose for this product. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent now or hereafter in existence. Under no circumstances shall 3D Systems, Inc. be liable for incidental, consequential, or other damages from alleged negligence, breach of warranty, strict liability or any other theory, arising out of the use or handling of this product. The sole liability of 3D Systems, Inc. for any claims arising out of the manufacture, use or sale of its products shall be for the buyer's purchase price.

The contents of this safety data sheet are subject to change without notice. 3D Systems, Inc. recommends that you periodically check www.3dsystems.com to make sure you are using the most current safety data sheet.

© Copyright 2008-2017 by 3D Systems, Inc. All rights reserved. Accura is a registered trademark, and the 3D logo is a trademark of 3D Systems, Inc.