Safety data sheet Breakaway

Ultimaker

1. Identification of the substance / preparation and of the company

1.1 Trade name Breakaway

1.2 Use of the product 3D printer filament

1.3 Supplier Ultimaker B.V.

Watermolenweg 2 4191 PN, Geldermalsen

The Netherlands

Emergency phone number In case of toxicological emergency, contact your doctor

2. Hazards identification according to regulation (EC) No 1272/2008 and GHS

2.1 Classification of the substance or mixture No risk exists to the health of users if the product is handled and

processed properly

2.2 Label elements -

2.3 Other hazards Not known

3. Composition / information on ingredients

3.1 Composition Not applicable

3.2 Mixture Thermoplastic polyurethane

Polylactic acid – CAS 9051-89-2

4. First-aid measures

4.1 Description of first-aid measures

General advice If you feel unwell, seek medical advice (show the label where

possible). Never give anything by mouth to an unconscious

person

Inhalation In case of inhalation of gases released from molten filament,

move person into fresh air

Skin contact Wash with soap and water. Seek medical attention if symptoms

occur. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water – do not try to peel it off. Seek medical attention, if necessary, for

removal and treatment of the burns

Eye contact Any material that contacts the eye should be washed out

immediately with water. If easy to do, remove contact lenses. Seek medical attention if symptoms persist. If molten material contacts the eye, immediately flush with plenty of water for at

least 15 minutes. Seek medical attention immediately

Ingestion Not probable. Seek medical advice in case ingestion occurs

Note to physician Treat symptomatically

4.2 Most important symptoms and effects, both acute and delayed

Burns should be treated as thermal burns. The material will come off as healing occurs; therefore immediate removal from skin is not necessary

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. Firefighting measures

substance or mixture

5.1 General advice Material can accumulate static charges which may cause an

electrical spark (ignition source). Use proper bonding and/or

grounding procedures

5.2 Extinguishing media Use dry chemical powder for small fires. For large fire use water

spray, fog, or foam

Unsuitable extinguishing media: water jet

5.3 Special hazards arising from theBurning produces unpleasant and toxic fumes: carbon oxides

(CO₂), nitrogen oxides (NO₂), hydrogen cyanide (HCN),

hydrocarbons

5.4 Advice for firefighters Use self-contained breathing apparatus and full protective

clothing

6. Accidental release measures

6.1 Personal precautions, protectiveequipment, and emergency procedures
Avoid breathing gases released from molten filament. Ensure adequate ventilation, especially in confined areas

6.2 Environmental precautionsNo data available

6.3 Methods and materials for containment Allow to solidify molten material. Dispose of waste and residue

according to local regulations

6.4 Reference to other sections

7. Handling and storage

7.1 Precautions for safe handling Avoid contact with molten material. Take precautionary measures

against static discharges

7.2 Conditions for safe storage, including any

incompatibilities

and cleaning up

Product should be stored in a dry and cool place at temperatures between -20 to +30 °C and below 50% relative humidity. Avoid direct sunlight. Take precautions to avoid static discharges

7.3 Specific end use(s) Filament for 3D printing

8. Exposure controls / personal protection

8.1 Control parameters None

DNEL No data available
PNEC No data available

8.2 Exposure controls

Eye protection Use safety glasses for prolonged staring at printing

Skin and body protection Good practices suggest to minimize skin contact. When material

is heated, wear gloves to protect against thermal burns

Respiratory protection If engineering controls do not maintain airborne concentrations

below recommended exposure limits (when applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: air-purifying respirator with an appropriate government-approved (where applicable) air-purifying filter, cartridge, or canister. Contact a health and safety professional or

manufacturer for specific information

Hand protection Follow good industrial hygiene practices
Hygiene measures Follow good industrial hygiene practices

Engineering measures Good general ventilation (typically 10 air changes per hour)

is recommended. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls that maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

acceptable level

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Filament

Color White

Odor Slight

Flash point -

Ignition temperature -

Thermal decomposition > 280 °C

Auto-ignition temperature Melting point / range -

Density $\sim 1.22 \text{ g/cm}^3$

Water solubility Insoluble

Solubility in other solvents -

9.2 Other information

10. Stability

Stable under recommended storage conditions

10.1 Reactivity Stable if stored and handled as indicated10.2 Chemical stability Stable if stored and handled as indicated

10.3 Possibility of hazardous reactions No decomposition or hazardous reactions if stored and applied

as directed

10.4 Conditions to avoid Print temperatures above 240 °C (at standard printing speeds).

Avoid all sources of ignition: heat, sparks, open flames, etc.

10.5 Incompatible materials Strong oxidizing agents

10.6 Hazardous decomposition products See 5.2

11. Toxicological information

11.1 Information on toxicological effects

Principal routes of exposure Eye contact, skin contact, inhalation, ingestion

Acute toxicity Not hazardous in normal industrial use

Skin corrosion / irritation Not irritating. Molten polymer will adhere to the skin,

thereby causing thermal burns

cause serious burns

Respiratory or skin sensitization No sensitization
Reproductive toxicity No data available
Carcinogenicity No data available

12. Ecological information

12.1 Toxicity No data available

12.2 Persistence and degradability No data available

12.3 Bio accumulative potential No data available

12.4 Mobility in soil No data available

12.5 Results of PBT and vPvB assessment No data available

12.6 Other adverse effects Not classified as environmentally hazardous. Disposal of large

contents could have a negative effect on the environment

13. Disposal considerations

13.1 Waste treatment methods In accordance with local and national regulations

14. Transport information

ADR Not regulated RID Not regulated IATA Not regulated IMDG Not regulated

Special precautions for user Keep away from strong oxidizers and sources of ignition

15. Regulatory information`

Not meant to be all-inclusive - selected regulations represented

15.1 Safety, health, and environmental regulations / legislation specific for the substance or mixture

US Regulations:

Sara 313 title III Not listed
TSCA Inventory List Not listed
OSHA hazard category Not listed
CERCLA Not listed
WHMIS Not listed
State right-to-know requirements Not listed

Other Inventories:

Canada DSL Inventory List Not listed **REACH / EU EINIECS** Not listed **NEHAPS** Not listed Not listed Japan (ECL/MITI) Australia (AICS) Not listed Korean toxic substances control act (ECL) Not listed Philippines inventory (PICCS) Not listed Not listed Chinese chemical inventory (IECSC)

15.2 Chemical Safety Assessment No data available

16. Other information

The information provided in this Safety Data Sheet (SDS) is based on current knowledge and experience. This information is provided without warranty. This information should help to make an independent determination of the methods to ensure proper and safe use and disposal of the filament

Version Version 1.003

Date January 14, 2019